



LATTICES DECORATIVE LOUVRES

LOUVRE TYPE

LOUVRE TYPE	Maximum recommended length*	A/C	B/C
Lattices (ref.2747)	2.0 meters	71%	44%
Decorative lattices (ref.2749)	1.5 meters	61%	34%
Clip lattices (ref.2829)	2.0 meters	100%	24%
Mini-lattices (ref.2785)	1.3 meters	55%	39%
Tubular louvres (ref.2847)	2.0 meters	76%	-
Decorative louvres (ref.9003)	6.5 meters	86%	-
Facade covering louvres (ref.500500)	-	-	-

* Depending on project specifications, it is possible to reach a longer louvre length (please consult).

WIND LOAD RESISTANCE

Shutter (Reference test 2.0 meters)

Wind loading resistance (EN 13659): **Class 6 (max.)**

Mini shutter (Reference test 1.3 meters)

Wind loading resistance (EN 13659): **Class 5**

Tubular louvre (Reference test 1.3 meters)

Wind loading resistance (EN 13659): **Class 6 (max.)**

EXTRUSION ALLOY

6063 T-5

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

